



PART	Material	Thickness of Chromium Plating	Hardness of Chromium plating	Roughness	Corrosion resistance (h) according to ISO10289	TOLERANCE REF: DOC-A087 RAW MATERIAL REF: DOC-A123
Rod	Ck45	>=20 µm	>=950 HV0,2	Ra<=0,2µm Rt <=2µm	200h NSS rating >=9	Drawing and technical data property of FAROIL srl
Tube	E355	////	////	Ra<=0,4µm	////	

CUSTOMER APPROVAL		Painting: BLACK RAL9005	Weight
APPROVED BY	APPROVAL DATE	Cylinder Marked FA MONTH/YEAR	5,65 kg

Max Working Pressure 220 Bar. Working temperature from -30C to +100C Max working speed 0,5 m/s

N°	DATE	MODIFICATION	DONE BY	N°	DATE	MODIFICATION	DONE BY
B	21/02/2019	Added thread M24x1,5 on port oil	Zaniboni				
A	15/01/2019	Was 316/20 +10 mm on sensor pos.	Giroldini				

FAROIL hydraulic cylinders	DESCRIPTION	DANI-TECH	CODE N°	INDEX	SCALE	DONE BY
	DOC-A116 Rev.C	CYLINDER Ø40/25x280	DK2188	B	////	21/02/2019
CUSTOMER REF.						P.D.
						E.B.

351840256	A	Sealing KIT Ø40/25	1
CODICE	REV.	DESCRIPTION	QTÀ