



Overfladebehandling:
Affædning efterfulgt af sort grundmaling.

Ikke målsat tolerancer jf.
DS/ISO 2768-v og 13920-B

Pos:	Drawing no:	Item No:	Description	Qty.	Weight (kg)
1	1002026	KO-MU-038-01	Muffe 3/8" for cylinder	1	0.042
2	1012958	61040411	Stempelstang 40 mm	1	2.155
3	1012959	Ej oprettet	Cylinderrør svejst	1	2.011
4	1010154	KO-PE-080-M27-01	Stempel ø80 M27x2,0 Lock NB	1	1.022
5	1010739	KO-TN-080-040-01	Indskruningshoved 80/40 NB	1	1.892
6	1011922	AF-H-035-01	Ledleje Ø35 GIHR-K-DO M28x1,5	1	1.237
7	1012367	KO-FU-080-035-01	Ledøje ø35 GE-DO m Ø80 bund	1	2.133

Pakningsæt er ikke vist

3D designer ha	3D Approved ha	Drawing no. 1012957	Date 02.02.2017	Scale 1:5	Size A3
2D drawing hsa	2D Approved hs	 Note			
 www.dani-tech.com			Description 8040100A035B035 Lmin= 380 mm Item no. CYL-0001317		
Proprietary and confidential. The information contained in this drawing is the sole property of Dani-tech Support ApS. Any reproduction in part or as a whole without the written permission of Dani-tech Support ApS is prohibited.		Max Pressure 220 Bar	Work temp. 0-70°C	Weight (kg) 10.493	