



PART	Material	Thickness of Chromium Plating	Hardness of Chromium plating	Roughness	Corrosion resistance (h) according to ISO10289	Drawing and technical data property of FAROIL srl
Rod	Ck45	>=20 µm	>=950 HV0,2	Ra<=0,2µm Rt <=2µm	120h NSS rating >=9	
Tube	E355	////	////	Ra<=0,4µm	////	
<b>CUSTOMER APPROVAL</b>				<b>Painting: BLACK PRIMER (NERO OPACO)</b>		<b>Weight</b>
APPROVED BY	APPROVAL DATE	<b>Cylinder Marked FA MONTH/YEAR</b>				<b>1,7 kg</b>
Max Working Pressure 220 Bar. Working temperature from -30C to +100C Max working speed 0,5 m/s						
N°	DATE	MODIFICATION	DONE BY	N°	DATE	MODIFICATION
FAROIL hydraulic cylinders		DANITECH		CODE N°		INDEX
TOLERANCE REF: DOC-A087		CYLINDER 25/16x200		DK1052		SCALE
DOC-A116 Rev.C		CUSTOMER REF.		DATE		05/01/2016
				DESIGNED BY		G.G.
				APPROVED BY		E.B.

Sealing Kit Code 35102516