



Kit valvola 3/8" Gas Int. 391 cod. 352520800
 per Valvola di Blocco Doppio Effetto
 "FPD 20L 2RO" cod.352010208

6.6	971000812	O-Ring DOWTY 812 (2,62x20,63)	1
6.5	977050034	Guarniz.pist.50/34 H.18,40	1
6.4	972000224	Anello Antiestr. DOWTY 224	1
6.3	971000224	O-Ring DOWTY 224 (3,53x44,04)	1
6.2	976300380	Guarniz.stelo 30/38/6,5	1
6.1	975000030	Raschiatore D. 30	1
6	35105030	Guarnizioni Cilindro 50/30	1
5	981201500	Dado Autob.BassoM20x1,5 DIN985	1
4	31050200	Pistone D.50 F.20 H.37	1
3	32050300	Testa 50/30 H.46	1
2	DK2753P2	Stelo cilindro 50/30x350	1
1	DK2753P1	Canna cilindro 50/30x350	1

POS.	CODICE	DESCRIZIONE	QTÀ
------	--------	-------------	-----

Finitura superficiale (Painting): BLUE RAL5017
 Max Pressione di esercizio (Max Working Pressure): 220 Bar
 Temperatura di lavoro (Working temperature) da (from) -30 C a (to) +80 C Velocità di lavoro (Max working speed) 0,5 m/s

N°		DATE	MODIFICATION	Approved by	N°	DATE	MODIFICATION	Approved by
DESCRIPTION		DANITECH		CODE N°		INDEX		SCALE
TOLERANCE REF: DOC-A087		Cylinder		DK2753				DATE
CUSTOMER REF.		50/30x350						DESIGNED BY
								APPROVED BY
								G.G.



Weight
9 kg

14/03/2014

M.M.

G.G.