









**WARNING!**

SECTIONS  OF THE ASSEMBLY MARKED ARE NOT SHIELDED AND MUST BE SHIELDED BY AN INTERACTIVE GUARDING SYSTEM. BONDIOLI & PAVESI DECLINES RESPONSIBILITY IF PROPER GUARDS ARE NOT PROVIDED OR MAINTAINED.

**DANGER!**  
*Assembly supplied without external yoke.  
 Customer must install yoke complies with applicable standards.*

**PERICOLO!**  
*Trasmissione fornita senza forcella di estremita'.  
 Il cliente deve installare una forcella conforme alle normative di sicurezza.*

PROTEGGERE I PERNI CON I TAPPI E FORNIRE I 2 CUSCINETTI E I 2 SEEGER A PARTE

1	CODICE CODE 007	LATO TRATTORE TRACTOR SIDE	LATO MACCHINA IMPLEMENT SIDE	TIPO-TYPE SFT-S8	CLIENTE / CUSTOMER 5200100 Egil Eng & Co.A/S	RIF. CLIENTE / CUSTOMER REF.	
2	CODICE CODE 000			DATA / DATE 31/5/2013	DISEGNATO / DESIGNED BY R. Moretti	TIPO DI MACCHINA / TYPE OF IMPLEMENT	
3	 L=835			LUNGHEZZA MAX IN LAVORO MAX WORKING LENGTH Lw=1410	STUDIO / DESIGN	ORIGINE / ORIGIN	
4	 L=855	VELOCITA' MAX MAX SPEED 540 min <sup>-1</sup>	M max 4000 Nm	LUNGHEZZA MAX TEMPORANEA MAX TEMPORARY LENGTH Lt=1543	NOTE / NOTES SPECIALE PER MANCANZA FORCELLA		
				LUNGHEZZA MAX NON IN ROTAZIONE MAX LENGTH AT STANDSTILL Ls=1610			REV. 0